



F-362A-P-PP

20.000 - 70.000 l/h Discs, cartridges, bags

Typical applications
Plating and process industry

Features

- Robust and service friendly
- Filter chamber with welded bottom (no seal)
- Thin discs (large filter area) or thick discs (large dirt holding capacity)
- Filter paper (thin/thick), cloth, cartridges (max. Ø 70mm) or bags
- Discs can be removed in manageable stacks
- All PP construction, max. temperature 80°C
- Wheels for portability
- External fasteners in SS316
- Unions for rigid piping (PP or CPVC sockets)

Options

- Hose connection
- Contact manometer
- Single open end cartridges
- Customised mounting plate
- External fasteners in titanium or electroless nickel coated



Filter chambers F362 PP



F	Medium	Material	In	Out
362A	K/P/B	PP	d75/DN63	

Selection: F - 362A - P - PP

maximum pressure				
°C	°F	Mpa	bar	psi
20	68	0,35	3,5	50
55	131	0,35	3,5	50
80	176	0,25	2,5	36

K = cartridges
Qty x L
362A-K = 36 x 20"

P = discs
Qty OD/ID m²
362A-P = 61 x 460/100 9
362A-Ph = 33 x 460/100 5

B = bags
Qty L/OD
362Z-B = 7 x 500/130